

## Air spring press

## for the assembly of air bellows

- > Compatible with the following brands: ContiTech, PHOENIX and PRIME-RIDE
- > For folding air springs and pressing bellows onto pistons
- > Time-saving thanks to fast and simple assembly
- Compact design, ergonomic handling
- Avoids damage to air springs
- > Ensures work safety in the workshop

Order options	
ASP 1 with barrel pump	incl. 2x8 sealing discs*
ASP 2 with barrel pump	incl. 2x2 sealing discs**
ASP 3 with hand pump	incl. 2x8 sealing discs*
ASP 4 with hand pump	incl. 2 x 2 sealing discs**

Technical data		
Design height		1500 mm
Width		450 mm
Depth		500 mm
Weight excl. pump		66 kg
Safety valve opening pressure		5 bar
*Sealing discs:	SD-102	Ø 102 - 96 mm
	SD-123	Ø 123 - 117 mm
	SD-132	Ø 132 - 126 mm
	SD-153	Ø 153 - 147 mm
	SD-168	Ø 168 - 162 mm
	SD-182	Ø 182 - 176 mm
	SD-192	Ø 192 - 186 mm
	SD-201	Ø 201 - 195 mm

<sup>\*\*</sup> incl. SD-132 and SD-153

## Included with delivery:

Air spring squeezer, hydraulic hose, pressure relief valve, quick venting function, 2x protective grids, 1x sealing disc base

List of compatible air spring systems available on request.







The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2020 ContiTech AG. All rights reserved. For complete information go to: www.continental-industry.com/discl\_en

